

Section 1. Identification

Manufacturer	Canadian supplier identifier	Transportation Emergency (CHEMTREC)	:	1-800-424-9300
CHS Inc.		Technical Information	:	1-651-355-8443
P.O. Box 64089		SDS Information	:	1-651-355-8445
Mail station 525				
St. Paul, MN 55164-0089				
Product name	: MAXTRON All Synthetic HD ATF	SDS no.	:	0207-907446
Common name	: Synthetic Automatic Transmission Fluid	Revision date	:	03/01/2023
Chemical name	: Lubricating oil.	Chemical formula	:	Mixture
Chemical family	: Hydrocarbon.			

Relevant identified uses of the substance or mixture and uses advised against

Synthetic transmission oil.

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).			
Classification of the substance or mixture	: ASPIRATION HAZARD - Category 1			
GHS label elements				
Hazard pictograms	:			
				
Signal word	: Danger			
Hazard statements	: H304 - May be fatal if swallowed and enters airways.			
Precautionary statements				
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.			
Prevention	: Not applicable.			
Response	: IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.			
Storage	: Store locked up.			
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.			
Hazards not otherwise classified	: None known.			
Hazardous Material Information System (U.S.A.)	Health :	1	/	Flammability : 1 Physical hazards : 0
National Fire Protection Association (U.S.A.)	Health :	1	Flammability :	1 Instability : 0

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture		
Chemical name	: Lubricating oil.		
Other means of identification	: Synthetic Automatic Transmission Fluid		

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	60 - 80	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	60 - 80	64742-54-7
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	10 - 30	68037-01-4
Diphenylamine	0.1 - 1	122-39-4

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. Get medical attention.
Inhalation	: If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible.
Skin contact	: If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.
Ingestion	: If material has been swallowed, do not induce vomiting. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation, watering, redness.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation, coughing.
Skin contact	: Adverse symptoms may include the following: irritation, redness.
Ingestion	: No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	: Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or water spray (fog) to extinguish fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Toxic fumes gases or vapors may evolve on burning.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.
Special protective equipment for fire-fighters	: Not applicable.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
------------------------------------	--

Methods and materials for containment and cleaning up

Spill	: Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.
--------------	--

Section 7. Handling and storage

Precautions for safe handling

Protective measures

- Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Advice on general occupational hygiene

- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Conditions for safe storage, including any incompatibilities

- Do not store above the following temperature: 80°C (175°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Do not store at temperatures exceeding 113°F (45°C). Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Diphenylamine	ACGIH TLV (United States, 3/2017). TWA: 10 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 10 mg/m³ 10 hours.

Canada

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³ 8 hours. Form: Mist STEV: 10 mg/m³ 15 minutes. Form: Mist CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³ 8 hours. Form: Mist STEV: 10 mg/m³ 15 minutes. Form: Mist CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 10 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 6/2017). TWA: 10 mg/m³ 8 hours.
Distillates (petroleum), hydrotreated heavy paraffinic	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³ 8 hours. Form: Mist STEV: 10 mg/m³ 15 minutes. Form: Mist CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³ 8 hours. Form: Mist STEV: 10 mg/m³ 15 minutes. Form: Mist CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 10 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 6/2017). TWA: 10 mg/m³ 8 hours.
Diphenylamine	CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.

Appropriate engineering controls : Use only with adequate ventilation.

Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Recommended: Splash goggles and a face shield, where splash hazard exists.
Skin protection	
Hand protection	: 4 - 8 hours (breakthrough time): Nitrile gloves.
Body protection	: Recommended: Long sleeved coveralls.
Other skin protection	: Recommended: Impervious boots.
Respiratory protection	: If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter.

Section 9. Physical and chemical properties

Appearance		
Physical state	: Liquid.	Relative density : 0.8443 to 0.8649
Color	: Red.	Evaporation rate : <1 (Ether. = 1)
Odor	: Mild petroleum.	Solubility : Insoluble in the following materials: cold water and hot water.
Odor threshold	: Not available.	Solubility in water : Insoluble
pH	: Not available.	Partition coefficient: n-octanol/water : Not available.
Melting point	: Not available.	Auto-ignition temperature : >260°C (>500°F)
Boiling point	: Not available.	Decomposition temperature : Not available.
Flash point	: Closed cup: >177°C (>350.6°F)	SADT : Not available.
Flammability	: Not available.	Viscosity : Not available.
Lower and upper explosive (flammable) limits	: Not available.	Vapor pressure : <0.13 kPa (<1 mm Hg) (68°F)
		Vapor density : Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Diphenylamine	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg 1120 mg/kg	- -

Irritation/Corrosion

Skin	: Not hazardous (per manufacturer).
Eyes	: Not hazardous (per manufacturer).
Respiratory	: Not hazardous (per manufacturer).

Sensitization

Skin	: Not hazardous (per manufacturer).
Respiratory	: Not hazardous (per manufacturer).

Mutagenicity

There is no data available.

Carcinogenicity

There is no data available.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Diphenylamine	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Lubricating oil.	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Dermal contact. Eye contact. Inhalation. Ingestion.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Diphenylamine	Acute EC50 2.17 mg/L Fresh water Acute EC50 0.31 mg/L Fresh water Acute LC50 2.2 ppm Fresh water Chronic NOEC 0.37 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase Daphnia - Daphnia magna Fish - Oncorhynchus mykiss Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours 48 hours 96 hours 72 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	>6.5	-	high
Diphenylamine	3.5	151.36	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : There is no data available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Section 14. Transport information

DOT IDENTIFICATION NUMBER	Not applicable.	DOT proper shipping name	Not applicable.
DOT Hazard Class(es)	Not applicable.	PG	Not applicable.
TDG IDENTIFICATION NUMBER	Not regulated.	TDG proper shipping name	Not applicable.
TDG Hazard Class(es)	Not applicable.	PG	Not applicable.

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) PAIR: Diphenylamine TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): All components are listed or exempted.
---------------------------------	--

Clean Air Act Section 602 Class I Substances	: Not listed	DEA List I Chemicals (Precursor Chemicals)	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed	DEA List II Chemicals (Essential Chemicals)	: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	: Not listed		

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Hazard classifications : ASPIRATION HAZARD - Category 1

Composition/information on ingredients

Name	Classification
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1

SARA 313 : This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Product name	CAS number	%
Not applicable.		

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light paraffinic
New York	: None of the components are listed.
New Jersey	: None of the components are listed.
Pennsylvania	: None of the components are listed.
California Prop. 65	

This product does not require a Safe Harbor warning under California Prop. 65.

Canadian lists	: All ingredients are listed on the Canadian Domestic Substances List (DSL), have been registered on the Non-Domestic Substances List (NDSL), or are exempt.
Canada inventory (DSL NDSL)	: All components are listed or exempted.
Canadian NPRI	: None of the components are listed.
CEPA Toxic substances	: None of the components are listed.

Section 16. Other information

Revision date : 03/01/2023
Revised Section(s) :

Supersedes : 04/11/2019
Prepared by : KMK Regulatory Services Inc.

Notice to reader

THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(q), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.



OUR ENERGY COMES THROUGH®

A BRAND OF The CHS logo consists of the letters 'CHS' in a stylized, italicized font with a registered trademark symbol.